



STREET & AREA LIGHTING

Specifications and Features:

Radiant™ LED

- Conformal Coating LED light engine
- CCT: 3000, 4000, 5000K

Optical

- Types I, II, III, IV, V

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- Dimmable Driver
- Surge Protection INCLUDED
 - surge protection device meets IEEE C62.41 2002 C High 10kA

Controls (adder)

- Button eye photo control (PC)
- 3-pin twist-lock receptacle (PCR3)
- 7-pin twist-lock receptacle (PCR7)

Housing

- Consists of a molded aluminum rim and a spun aluminum canopy that combine for a sleek and compact appearance.
- Side Mount on a horizontal tenon

Finish

- Super durable polyester powder coat finish over a chromate conversion coating. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location

Warranty

- 5 year limited warranty



EPA: 1.6
 WEIGHT: 32 lbs (max.)

ORDERING FORMAT

Example: VEN1-NL-70W4K-U-5-SM-N-BK

VEN1		NL			
Model	Globe/Lens	LED Module	Voltage	Distribution	
VEN1=Side-Mount Ventura	NL= No Secondary Lens	See Chart - LED Light Engine Specifications.	U=120-277V H=347/480V	1=Type I 2=Type II 3=Type III 4=Type IV 5=Type V	
SM					
Mounting	Options	Finish			
SM=Side Mount	FS=Fuse, Single PC=Button Eye Photo Control PCR3=3-Pin Twist-Lock Receptacle PCR7=7-Pin Twist-Lock Receptacle N=None	Standard Colors BK=Black BZ=Bronze DBZ=Dark Bronze WH=White	Standard Colors GR=Green SM=Silver Metallic GY=Light Grey TBK=Textured Black	CC=Custom (Consult Factory)	



STREET & AREA LIGHTING



13" Radiant™



12" Radiant™



8" Radiant™

Lumen Output for Radiant™

CCT	LED Module	Input Watts	Efficacy Range		Type 2	Type 3	Type 4	Type 5
5K	40W5K	40	131	138	5091	5100	4925	5202
	50W5K	50	118	123	6311	6314	6076	6367
	60W5K	60	117	125	7012	6884	6756	7201
	70W5K	70	110	116	7262	7415	7282	7713
	80W5K	80	110	116	8300	8474	8322	8815
	90W5K	90	110	116	9337	9533	9362	9917
	105W5K	105	131	128	12793	12470	12656	12507
	120W5K	120	131	128	14620	14252	14464	14294
	135W5K	135	131	128	16448	16033	16272	16081
4K	40W4K	40	126	133	4913	4922	4753	5020
	50W4K	50	113	119	6090	6093	5863	6144
	60W4K	60	113	120	6767	6643	6520	6949
	70W4K	70	106	112	7008	7155	7026	7443
	80W4K	80	106	112	8009	8177	8030	8506
	90W4K	90	106	112	9010	9199	9034	9570
	105W4K	105	127	124	12345	12034	12213	12070
	120W4K	120	127	124	14109	13753	13958	13794
	135W4K	135	127	124	15872	15472	15702	15518
3K	40W3K	40	121	128	4735	4743	4580	4838
	50W3K	50	109	115	5869	5872	5651	5921
	60W3K	60	109	116	6521	6402	6283	6697
	70W3K	70	102	108	6754	6896	6772	7173
	80W3K	80	102	108	7719	7881	7739	8198
	90W3K	90	102	108	8683	8866	8707	9223
	105W3K	105	122	119	11897	11597	11770	11632
	120W3K	120	122	119	13597	13254	13452	13294
	135W3K	135	122	119	15297	14911	15133	14955

*Please refer to the fixture's IES file for detailed information. Subject to change.



STREET & AREA LIGHTING

