



POST TOP LUMINAIRES



Specifications and Features:

Radiant™ LED

- Conformal Coating LED light engine
- CCT: Amber, LPS (1800K), 2200K, 2700K, 3000K, 4000K, 5000K
- Static Colors Available - Contact Factory

Distribution

- Types II, III, IV, V

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10V Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (Optional)

- Button eye photo control (PC)
- House Side Shield (H)

Housing

- Cast aluminum cage & roof

Finish

- Super durable polyester powder coat finish. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location and IP66
- LED is IP66 Rated

Warranty

- 5 year limited warranty

EPA: 2.7
 WEIGHT: 40 lbs (max.)

Order Information Example:		CARL3FA50W4KU5JNNBK		
Model	Globe/Lens	LED Module	Voltage	Distribution
CARL3=Carlsbad3	CA=Clear Acrylic, CP=Clear Polycarbonate FA=Frosted Acrylic, FP=Frosted Polycarbonate TG=Flat Tempered Glass, Clear, FG=Flat Tempered Glass, Frosted WA=White (Opal) Acrylic, PA=Pattern Acrylic, DA=Seeded Acrylic	See Chart on Page 2	U=120-277V H=347/480V	2=Type II 3=Type III 4=Type IV 5=Type V
Finial	Mounting	Options	Finish (Standard)	
J=GF10 (Standard), B=GF2, C=GF3, D=GF4, F=GF6, G=GF7, H=GF8, I=GF9, K=GF12, O=GF17, P=GF18, V=GF24, N=None	N=None (Standard Post Top) WM=Wall Mount PEN2=Pendant Mount for chain hanging PEN3=Pendant Mount for stem hanging	PC=Button Eye Photo Control H=House Side Shield N=None	BK=Black, BZ=Bronze, DBZ=Dark Bronze, WH=White GR=Green, SM=Silver Metallic, GY=Light Gray TBK=Textured Black, CC=Custom Color (Consult Factory)	



POST TOP LUMINAIRES



6" Radiant™



8" Radiant™


6" & 8" Radiant Lumen Chart						
Initial lumen data						
CCT	LED Module	Input Watts	Type 2	Type 3	Type 4	Type 5
5K	10W5K	10	1217	1186	1204	1190
	15W5K	15	1826	1780	1806	1785
	20W5K	20	2434	2373	2408	2380
	30W5K	30	3651	3559	3612	3570
	40W5K	40	5091	5100	4925	5202
	60W5K	60	6311	6314	6076	6367
4K	10W4K	10	1175	1145	1162	1148
	15W4K	15	1762	1717	1743	1723
	20W4K	20	2349	2290	2324	2297
	30W4K	30	3524	3435	3486	3445
	40W4K	40	4913	4922	4753	5020
	60W4K	60	6090	6093	5863	6144
3K	10W3K	10	1132	1103	1120	1107
	15W3K	15	1698	1655	1680	1660
	20W3K	20	2264	2207	2240	2213
	30W3K	30	3396	3310	3360	3320
	40W3K	40	4735	4743	4580	4838
	60W3K	60	5869	5872	5651	5921
27K	10W27K	10	1098	1070	1086	1073
	15W27K	15	1647	1605	1629	1610
	20W27K	20	2196	2141	2172	2147
	30W27K	30	3294	3211	3259	3220
	40W27K	40	4392	4281	4345	4294
	60W27K	60	5490	5351	5431	5367
			6588	6422	6517	6441

This chart indicates INITIAL LUMENS. Globe/Lens choice will affect lumen output.

Contact the factory for Amber, LPS and 2200K lumen output



POST TOP LUMINAIRES





POST TOP LUMINAIRES



Finials



GF2 - 6"



GF3 - 6"



GF4 - 6"



GF6 - 4"



GF7 - 4.5"



GF8 - 4"



GF9 - 4.25"



GF10 - 3.5"



GF12 - 2.75"



GF17 - 4"



GF18 - 2.75"



GF24 - 4.75"