



LED POST TOPS



EPA: 1.8
 WEIGHT: 38 lbs (max.)

Specifications and Features:

Radiant™ LED

- Conformal Coating LED light engine
- CCT: Amber, LPS (1800K), 2200K, 2700K, 3000K, 4000K, 5000K
- Static Colors Available - Contact Factory

Optical

- Types I* II, III, IV, V (Type I available in 70w & higher only)

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10V Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (adder)

- Button eye photo control (PC)

Housing

- Cast aluminum cage, roof and 3" slip fitter*

Finish

- Super durable polyester powder coat finish over a chromate conversion coating. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location and IP66
- LED is IP66 Rated

Warranty

- 5 year limited warranty

Order Information Example:

HOL	Model	Globe/Lens	LED Module	Voltage	Distribution	Options	Finish (Standard Colors)
HOL=Holland		CA=Clear Acrylic CP=Clear Polycarbonate FA=Frosted Acrylic FP=Frosted Polycarbonate TG=Flat Tempered Glass, Clear FG=Flat Tempered Glass, Frosted WA=White (Opal) Acrylic PA=Pattern Acrylic	See Chart on Page 2	U=120-277V H=347/480V	1=Type I* 2=Type II 3=Type III 4=Type IV 5=Type V *70W & above only	PC=Button eye photo control N=None	BK=Black BZ=Bronze DBZ=Dark Bronze WH=White GR=Green SM=Silver Metallic GY=Light Gray TBK=Textured Black CC=Custom Color (Consult Factory)



LED POST TOPS



12" Radiant™

8" Radiant™

RADIANT™

LED LIGHT ENGINE SPECIFICATIONS:						
LED Module	Wattage	Nominal Lumens*	System Efficacy	CCT	CRI	IES Distributions
40W5K	40	4,396	109.9	5000K	85	Type II, III, IV, V
50W5K	50	5,495	109.9	5000K	85	Type II, III, IV, V
60W5K	60	6,594	109.9	5000K	85	Type II, III, IV, V
70W5K	70	7,693	109.9	5000K	85	Type II, III, IV, V
80W5K	80	8,792	109.9	5000K	85	Type II, III, IV, V
40W4K	40	4,396	109.9	4000K	85	Type II, III, IV, V
50W4K	50	5,495	109.9	4000K	85	Type II, III, IV, V
60W4K	60	6,594	109.9	4000K	85	Type II, III, IV, V
70W4K	70	7,693	109.9	4000K	85	Type II, III, IV, V
80W4K	80	8,792	109.9	4000K	85	Type II, III, IV, V
40W3K	40	4,396	109.9	3000K	85	Type II, III, IV, V
50W3K	50	5,495	109.9	3000K	85	Type II, III, IV, V
60W3K	60	6,594	109.9	3000K	85	Type II, III, IV, V
70W3K	70	7,693	109.9	3000K	85	Type II, III, IV, V
80W3K	80	8,792	109.9	3000K	85	Type II, III, IV, V

*Please refer to the fixture's IES file for detailed information. Subject to change.

Contact the factory for Amber, LPS and 2200K lumen output



LED POST TOPS

