



LED PENDANT MOUNT



Specifications and Features:

Radiant™ LED

- Conformal Coating LED light engine
- CCT: Amber, LPS (1800K), 2200K, 2700K, 3000K, 4000K, 5000K
- Static Colors Available - Contact Factory

Distribution

- Types I* II, III, IV, V (Type I available in 70w & higher only)
- Full Cutoff

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10v Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (Optional)

- Button eye photo control (PC)
- House Side Shield (H)

Housing

- Cast aluminum upper dome & spun aluminum lower shade

Finish

- Super durable polyester powder coat finish. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location.
- LED is IP66 Rated

Warranty

- 5 year limited warranty

EPA: 2.4
 WEIGHT: 36 lbs (max.)

Order Information Example:

FLOR3NL70W4KU3PCBK

FLOR3						
Model	Globe/Lens	LED Module	Voltage	Distribution	Options	Finish (Standard Colors)
FLOR3= Florence 3 Radiant	NL=No Secondary Lens	See Chart on Page 2	U=120-277V H=347/480V	1=Type I* 2=Type II 3=Type III 4=Type IV 5=Type V *70W & above only	N=None PC=Button Eye Photo Control H=House Side Shield	BK=Black BZ=Bronze DBZ=Dark Bronze WH=White GR=Green SM=Silver Metallic GY=Light Gray TBK=Textured Black CC=Custom Color (Consult Factory)



LED PENDANT MOUNT



13" Radiant™



12" Radiant™



8" Radiant™

Lumen Output for Florence III Radiant

CCT	LED Module	Input Watts	Efficacy Range		Type 2	Type 3	Type 4	Type 5	CCT	LED Module	Input Watts	Efficacy Range		Type 2	Type 3	Type 4	Type 5
5K	40W5K	40	131	138	5091	5100	4925	5202	3K	40W3K	40	121	128	4735	4743	4580	4838
	50W5K	50	118	123	6311	6314	6076	6367		50W3K	50	109	115	5869	5872	5651	5921
	60W5K	60	117	125	7012	6884	6756	7201		60W3K	60	109	116	6521	6402	6283	6697
	70W5K	70	110	116	7262	7415	7282	7713		70W3K	70	102	108	6754	6896	6772	7173
	80W5K	80	110	116	8300	8474	8322	8815		80W3K	80	102	108	7719	7881	7739	8198
	90W5K	90	110	116	9337	9533	9362	9917		90W3K	90	102	108	8683	8866	8707	9223
	105W5K	105	131	128	12793	12470	12656	12507		105W3K	105	122	119	11897	11597	11770	11632
	120W5K	120	131	128	14620	14252	14464	14294		120W3K	120	122	119	13597	13254	13452	13294
	135W5K	135	131	128	16448	16033	16272	16081		135W3K	135	122	119	15297	14911	15133	14955
4K	40W4K	40	126	133	4913	4922	4753	5020	27K	40W27K	40	121	128	4640	4648	4489	4741
	50W4K	50	113	119	6090	6093	5863	6144		50W27K	50	109	115	5752	5755	5538	5803
	60W4K	60	113	120	6767	6643	6520	6949		60W27K	60	109	116	6391	6274	6157	6563
	70W4K	70	106	112	7008	7155	7026	7443		70W27K	70	102	108	6619	6758	6637	7030
	80W4K	80	106	112	8009	8177	8030	8506		80W27K	80	102	108	7564	7723	7584	8034
	90W4K	90	106	112	9010	9199	9034	9570		90W27K	90	102	108	8510	8688	8533	9038
	105W4K	105	127	124	12345	12034	12213	12070		105W27K	105	122	119	11659	11365	11535	11399
	120W4K	120	127	124	14109	13753	13958	13794		120W27K	120	122	119	13325	12989	13183	13028
	135W4K	135	127	124	15872	15472	15702	15518		135W27K	135	122	119	14991	14612	14830	14656

Contact the factory for Amber, LPS and 2200K lumen output



LED PENDANT MOUNT

