



POST TOPS



Image above shows Huntington with Opti-FLUX LED

Specifications and Features:

Opti-FLUX™ & Radiant™ LED

- Conformal Coating LED light engine
- CCT: Amber, LPS (1800K), 2200K, 2700K, 3000K, 4000K, 5000K (HUNT1 only)
- Static Colors Available - Contact Factory (HUNT 1 only)

Distribution

- Types I* II, III, IV, V (Type I available in 70w & higher only-HUNT 1only)

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10V Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (Adder)

- Button eye photo control (PC)
- House Side Shield (H)
- 3-pin twist-lock receptacle (PCR3)**
- 7-pin twist-lock receptacle (PCR7)**

Housing

- Decorative capital housing choices with 3" slip fitter

Finish

- Super durable polyester powder coat finish over a conversion coating. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location

Warranty

EPA: 2.7
 WEIGHT: 40 lbs (max.)

Order Information Example:

HUNT1SAC160W4KU3A1NPCBK

| Model | Globe/Lens | Capital | LED Module | Voltage |
|--|--|--|---|--|
| HUNT=Huntington Opti-FLUX with Globe HUNT1=Huntington Radiant with Spinning | SA=Stippled Acrylic SP=Stippled Polycarbonate N=No Globe (Radiant LED) | C1=PLC1, C2=PLC2, C3=PLC3, C4=PLC4, C5=PLC5, C6=PLC6, C7=PLC7, C8=PLC8, C9=PLC9, C10=PLC10, C11=PLC11 | See Chart on Page 2 & 3 | U=120-277V H=347/480V |
| Distribution | Bands & Cages | Spinning | Options | Finish |
| 1=Type I* 2=Type II 3=Type III 4=Type IV 5=Type V *70W & above only | A1=DECA1 A2=DECA2 A3=DECA3 A5=DECA5 A6=DECA6 N=None | T2=T102 N=None *Must use T2 spinning if ordering Huntington 1 (Radiant LED) | PC=Button Eye Photo Control H=House Side Shield PCR3=3 Pin Twist Lock Receptable (photo cell not included)* PCR7=7 Pin Twist Lock Receptable (photo cell not included)* N=None *C8, C10 Capital Only | BK=Black BZ=Bronze DBZ=Dark Bronze WH=White GR=Green SM=Silver Metallic GY=Light Gray TBK=Textured Black CC=Custom Color (Consult Factory) |



POST TOPS



“Opti-FLUX™ LED Light Engine”

| HUNTINGTON Opti-FLUX™ Stipple Globe | | | | | Type 3 | | Type 5 | |
|-------------------------------------|------------|-------------|----------------|----|---------------------|-----------------------|---------------------|-----------------------|
| | LED Module | Input Watts | Efficacy Range | | T1, T3, T4-Spun Top | Open Acrylic/Poly Lid | T1, T3, T4-Spun Top | Open Acrylic/Poly Lid |
| 5K | 32W5K | 32 | 77 | 86 | 2680 | 2869 | 2836 | 2976 |
| | 40W5K | 40 | 77 | 86 | 3350 | 3587 | 3545 | 3719 |
| | 48W5K | 48 | 77 | 86 | 4020 | 4304 | 4254 | 4463 |
| | 56W5K | 56 | 77 | 86 | 4690 | 5021 | 4963 | 5207 |
| | 64W5K | 64 | 77 | 86 | 5360 | 5739 | 5672 | 5951 |
| | 72W5K | 72 | 77 | 86 | 6030 | 6456 | 6381 | 6695 |
| | 80W5K | 80 | 77 | 86 | 6700 | 7174 | 7090 | 7439 |
| | 88W5K | 88 | 77 | 86 | 7370 | 7891 | 7799 | 8183 |
| | 96W5K | 96 | 77 | 86 | 8040 | 8608 | 8508 | 8927 |
| 4K | 32W4K | 32 | 72 | 80 | 2487 | 2663 | 2632 | 2761 |
| | 40W4K | 40 | 72 | 80 | 3109 | 3328 | 3289 | 3451 |
| | 48W4K | 48 | 72 | 80 | 3730 | 3994 | 3947 | 4142 |
| | 56W4K | 56 | 72 | 80 | 4352 | 4660 | 4605 | 4832 |
| | 64W4K | 64 | 72 | 80 | 4974 | 5325 | 5263 | 5522 |
| | 72W4K | 72 | 72 | 80 | 5596 | 5991 | 5921 | 6213 |
| | 80W4K | 80 | 72 | 80 | 6217 | 6657 | 6579 | 6903 |
| | 88W4K | 88 | 72 | 80 | 6839 | 7322 | 7237 | 7593 |
| | 96W4K | 96 | 72 | 80 | 7461 | 7988 | 7895 | 8283 |
| 3K | 32W3K | 32 | 65 | 72 | 2251 | 2410 | 2382 | 2499 |
| | 40W3K | 40 | 65 | 72 | 2814 | 3013 | 2978 | 3124 |
| | 48W3K | 48 | 65 | 72 | 3377 | 3615 | 3573 | 3749 |
| | 56W3K | 56 | 65 | 72 | 3940 | 4218 | 4169 | 4374 |
| | 64W3K | 64 | 65 | 72 | 4502 | 4821 | 4764 | 4999 |
| | 72W3K | 72 | 65 | 72 | 5065 | 5423 | 5360 | 5624 |
| | 80W3K | 80 | 65 | 72 | 5628 | 6026 | 5955 | 6249 |
| | 88W3K | 88 | 65 | 72 | 6191 | 6628 | 6551 | 6873 |
| | 96W3K | 96 | 65 | 72 | 6754 | 7231 | 7146 | 7498 |



POST TOPS



13" Radiant™



12" Radiant™



8" Radiant™

| Huntington 1 Radiant Lumen Chart (HUNT1) | | | | | | | | |
|--|------------|-------------|----------------|-------|---------|----------|---------|--------|
| Color Temp | LED Module | Input Watts | Efficacy Range | | Type II | Type III | Type IV | Type V |
| 5K | 40W5K | 40 | 117 | 124 | 4669 | 4767 | 4681 | 4959 |
| | 50W5K | 50 | 118 | 125 | 5882 | 6006 | 5898 | 6248 |
| | 60W5K | 60 | 117 | 124 | 7003 | 7150 | 7022 | 7438 |
| | 70W5K | 70 | 117 | 125 | 8217 | 8389 | 8239 | 8727 |
| | 80W5K | 80 | 117 | 124 | 9337 | 9533 | 9362 | 9917 |
| | 90W5K | 90 | 117 | 125 | 10551 | 10772 | 10579 | 11206 |
| | 105W5K | 105 | 117 | 125 | 12325 | 12584 | 12358 | 13090 |
| | 120W5K | 120 | 117 | 124 | 14006 | 14300 | 14043 | 14876 |
| 4K | 40W4K | 40 | 105 | 111 | 4188 | 4276 | 4199 | 4448 |
| | 50W4K | 50 | 106 | 112 | 5276 | 5387 | 5291 | 5604 |
| | 60W4K | 60 | 105 | 111 | 6281 | 6413 | 6298 | 6672 |
| | 70W4K | 70 | 105 | 112 | 7370 | 7525 | 7390 | 7828 |
| | 80W4K | 80 | 105 | 111 | 8375 | 8551 | 8398 | 8896 |
| | 90W4K | 90 | 105 | 112 | 9464 | 9663 | 9489 | 10052 |
| | 105W4K | 105 | 105 | 112 | 11055 | 11287 | 11085 | 11742 |
| | 120W4K | 120 | 105 | 111 | 12563 | 12827 | 12597 | 13343 |
| 3K | 40W3K | 40 | 95 | 100 | 3781 | 3861 | 3792 | 4016 |
| | 50W3K | 50 | 95 | 101 | 4765 | 4865 | 4777 | 5061 |
| | 60W3K | 60 | 95 | 100 | 5672 | 5791 | 5687 | 6025 |
| | 70W3K | 70 | 95 | 101 | 6655 | 6795 | 6673 | 7069 |
| | 80W3K | 80 | 95 | 100 | 7563 | 7722 | 7583 | 8033 |
| | 90W3K | 90 | 95 | 101 | 8546 | 8726 | 8569 | 9077 |
| | 105W3K | 105 | 95 | 101 | 9983 | 10193 | 10010 | 10603 |
| | 120W3K | 120 | 95 | 100 | 11344 | 11583 | 11375 | 12049 |
| 27K | 40W27K | 40 | 93 | 99 | 3711 | 3789 | 3721 | 3942 |
| | 50W27K | 50 | 94 | 99 | 4676 | 4775 | 4689 | 4967 |
| | 60W27K | 60 | 93 | 99 | 5567 | 5684 | 5582 | 5913 |
| | 70W27K | 70 | 93 | 99 | 6532 | 6669 | 6550 | 6938 |
| | 80W27K | 80 | 93 | 99 | 7423 | 7579 | 7443 | 7884 |
| | 90W27K | 90 | 93 | 99 | 8388 | 8564 | 8410 | 8909 |
| | 105W27K | 105 | 93 | 99 | 9798 | 10004 | 9824 | 10407 |
| | 120W27K | 120 | 93 | 99 | 11134 | 11368 | 11164 | 11826 |
| 135W27K | 135 | 93 | 99 | 12545 | 12808 | 12578 | 13324 | |

Contact the factory for Amber, LPS and 2200K lumen output



POST TOPS



Capitals



PLC1 - 8 3/4" High



PLC2 - 10 13/16" High



PLC3 - 6 7/8" High



PLC4 - 7 13/16" High



PLC5 - 9 15/16" High



PLC6 - 8 1/16" High



PLC7 - 8 3/8" High



PLC8 - 11 3/8" High



PLC9 - 14 1/4" High



PLC10 - 10 1/4" High



PLC11 - 15" High



POST TOPS
MADE IN THE USA

Bands & Cages



A1 - Cast Aluminum Perforated Cage



A2 - Cast Aluminum Band



A3 - Cast Aluminum Cage



A5 - Cast Aluminum Cage



A6 - Cast Aluminum Cage



A6M - A6 Cage with Medallions*

*A1, A5, and A6 are available with Medallions. Add M to the end of the part number.

Spinnings



T2 - T102 Top Spinning
 (Must choose this if using Radiant LED)



POST TOPS



Stipple Globe

