



## POST TOPS



Photo shown with C1 capital, A1 cage, T3 Spinning, no finial & no secondary lens

## Specifications and Features:

### Radiant™ LED

- Conformal Coating LED light engine
- CCT: Amber, LPS (1800K), 2200K, 2700K, 3000K, 4000K, 5000K
- Static Colors Available - Contact Factory

### Distribution

- Types I\* II, III, IV, V (Type I available in 70w & higher only)
- Full Cutoff

### Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10v Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

### Controls (Optional)

- Button eye photo control (PC)
- 3-pin twist-lock receptacle (PCR3)\*\*
- 7-pin twist-lock receptacle (PCR7)\*\*

### Housing

- Choice of multiple cast decorative housings with 3" slip fit.

### Finish

- Super durable polyester powder coat finish. Custom finishes available, including patinas and all RAL colors.

### Listings & Ratings

- ETL listed to UL 1598 standard for wet location.

### Warranty

- 5 year limited warranty

EPA: 2.2  
WEIGHT: 32 lbs (max.)

**Order Information Example:** LEXNLC560W4KU3A1T2PCFBK

LEX	NL				
Model	Globe/Lens	Capital	LED Module	Voltage	Distribution
LEX=Lexington Post Top	NL=No Secondary Lens	C1=PLC1, C2=PLC2, C3=PLC3, C4=PLC4, C5=PLC5, C6=PLC6 C7=PLC7, C8=PLC8, C9=PLC9, C10=PLC10, C11=PLC11	See Chart on Page 2 & 3	U=120-277V H=347/480V	1=Type I* 2=Type II 3=Type III 4=Type IV 5=Type V  *70W & above only
Bands & Cages	Spinning	Options	Finial	Finish	
A1=DECA1 (Standard) A3=DECA3 A6=Perforated Band w/Cage A7=Flat Band w/Cage	T2=T102 (Standard) T3=T103 T4=T104	PC=Button Eye Photo Control PCR3=3 Pin Twist Lock Receptable (photo cell not included)* PCR7=7 Pin Twist Lock Receptable (photo cell not included)* N=None  *C8, C10 Capital Only	E=GF5 (Standard) B=GF2, C=GF3, D=GF4, F=GF6 G=GF7, H=GF8, I=GF9, J=GF10, K=GF12, O=GF17, P=GF18, V=GF24 N=None	BK=Black BZ=Bronze DBZ=Dark Bronze WH=White GR=Green SM=Silver Metallic GY=Light Gray TBK=Textured Black CC=Custom Color (Consult Factory)	



**POST TOPS**



13" Radiant™



12" Radiant™



8" Radiant™

**Lumen Output for Lexington**

**No Secondary Lens**

CCT	LED Module	Input Watts	Type 2	Type 3	Type 4	Type 5
5K	40W5K	40	4036	4110	4178	4288
	50W5K	50	5047	5091	5175	5312
	60W5K	60	6008	6060	6160	6323
	70W5K	70	7068	7130	7247	7439
	80W5K	80	8072	8142	8276	8496
	90W5K	90	9083	9162	9313	9559
	105W5K	105	10373	10463	10635	11159
120W5K	120	11672	11773	11967	12751	
4K	40W4K	40	3844	3877	3941	4046
	50W4K	50	4807	4848	4928	5059
	60W4K	60	5722	5772	5867	6022
	70W4K	70	6732	6790	6902	7085
	80W4K	80	7688	7755	7882	8091
	90W4K	90	8650	8726	8869	9104
	105W4K	105	9879	9965	10129	10628
120W4K	120	11116	11212	11397	12144	
3K	40W3K	40	3690	3722	3784	3884
	50W3K	50	4614	4654	4731	4856
	60W3K	60	5493	5541	5632	5781
	70W3K	70	6463	6519	6626	6802
	80W3K	80	7380	7444	7567	7767
	90W3K	90	8304	8377	8515	8740
	105W3K	105	9484	9566	9724	10202
120W3K	120	10671	10764	10941	11658	
27K	40W27K	40	3460	3490	3547	3641
	50W27K	50	4326	4364	4435	4553
	60W27K	60	5150	5195	5280	5420
	70W27K	70	6059	6111	6212	6377
	80W27K	80	6919	6979	7094	7282
	90W27K	90	7785	7853	7982	8194
	105W27K	105	8891	8968	9116	9565
120W27K	120	10004	10091	10257	10929	

**Contact the factory for  
 Amber, LPS and 2200K  
 lumen output**



**POST TOPS**



**Capitals**



PLC1 - 8 3/4" High



PLC2 - 10 13/16" High



PLC3 - 6 7/8" High



PLC4 - 7 13/16" High



PLC5 - 9 15/16" High



PLC6 - 8 1/16" High



PLC7 - 8 3/8" High



PLC8 - 11 3/8" High



PLC9 - 14 1/4" High



PLC10 - 10 1/4" High



PLC11 - 15" High

**Bands & Cages**



A1 - Cast Aluminum Perforated Cage



A3 - Cast Aluminum Cage



A6 - Cast Aluminum Cage w/ Perforated Band



A7 - Cast Aluminum Cage w/ Flat Band



A6M - Cage with Medallions\*

\*A1, A6, and A7 are available with Medallions. Add M to the end of the part number.



**POST TOPS**



**Spinnings**



T1 - T101 Top Spinning



T3 - T103 Top Spinning



T4 - T104 Top Spinning

**Fixture Finials**



GF2 - 6"



GF3 - 6"



GF4 - 6"



GF5 (plastic)  
GF6 (cast) - 4"



GF7 - 4.5"



GF8 - 4"



GF9 - 4.25"



GF10 - 3.5"



GF12 - 2.75"



GF17 - 4"



GF18 - 2.75"



GF24 - 4.75"



## POST TOPS

