



POST TOP LUMINAIRES



Specifications and Features:

Radiant™ LED

- Conformal Coating LED light engine
- CCT: Amber, LPS (1800K), 2200K, 2700K, 3000K, 4000K, 5000K
- Static Colors Available - Contact Factory

Distribution

- Types I* II, III, IV, V (Type I available in 70w & higher only)
- Full Cutoff

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10v Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (Optional)

- Button eye photo control (PC)

Housing

- Spun aluminum roof, sand cast arms and capital.
- 3" slip fitter.

Finish

- Super durable polyester powder coat finish. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location.
- LED is IP66 Rated

Warranty

- 5 year limited warranty

EPA: 2.5
 WEIGHT: 38 lbs (max.)

Order Information Example: SLSNLC670W4KU5NNBK

SLS	NL	C6					
Model	Globe/Lens	Capital	LED Module	Voltage	Distribution	Options	Finish (Standard Colors)
SLS=Salinas	NL=No Secondary Lens	C6=PLC6	See Chart on Page 2	U=120-277V H=347/480V	1=Type I* 2=Type II 3=Type III 4=Type IV 5=Type V *70W & above only	N=None PC=Button Eye Photo Control	BK=Black BZ=Bronze DBZ=Dark Bronze WH=White GR=Green SM=Silver Metallic GY=Light Gray TBK=Textured Black CC=Custom Color (Consult Factory)



POST TOP LUMINAIRE



13" Radiant™



12" Radiant™



8" Radiant™

Lumen Output for Salinas						
No Secondary Lens						
CCT	LED Module	Input Watts	Type 2	Type 3	Type 4	Type 5
5K	40W5K	40	4036	4110	4178	4288
	50W5K	50	5047	5091	5175	5312
	60W5K	60	6008	6060	6160	6323
	70W5K	70	7068	7130	7247	7439
	80W5K	80	8072	8142	8276	8496
	90W5K	90	9083	9162	9313	9559
	105W5K	105	10373	10463	10635	11159
4K	120W5K	120	11672	11773	11967	12751
	40W4K	40	3844	3877	3941	4046
	50W4K	50	4807	4848	4928	5059
	60W4K	60	5722	5772	5867	6022
	70W4K	70	6732	6790	6902	7085
	80W4K	80	7688	7755	7882	8091
	90W4K	90	8650	8726	8869	9104
3K	105W4K	105	9879	9965	10129	10628
	120W4K	120	11116	11212	11397	12144
	40W3K	40	3690	3722	3784	3884
	50W3K	50	4614	4654	4731	4856
	60W3K	60	5493	5541	5632	5781
	70W3K	70	6463	6519	6626	6802
	80W3K	80	7380	7444	7567	7767
27K	90W3K	90	8304	8377	8515	8740
	105W3K	105	9484	9566	9724	10202
	120W3K	120	10671	10764	10941	11658
	40W27K	40	3460	3490	3547	3641
	50W27K	50	4326	4364	4435	4553
	60W27K	60	5150	5195	5280	5420
	70W27K	70	6059	6111	6212	6377
27K	80W27K	80	6919	6979	7094	7282
	90W27K	90	7785	7853	7982	8194
	105W27K	105	8891	8968	9116	9565
	120W27K	120	10004	10091	10257	10929

Contact the factory for Amber, LPS and 2200K lumen output



POST TOP LUMINAIRES

