




## LED POST TOP LUMINAIRES



Close Up of Prismatic Globe.

LEX2 with C1 Capital, A1 Cage, T3  
Top Spinning and No Finial

### Specifications and Features:

#### Opti-FLUX™ LED

- CCT: 2700K, 3000K, 4000K, 5000K

#### Distribution

- Types III & V

#### Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- Standard Surge Protection Included (6kV Line-Line; 10kV Line-Earth)

#### Controls (Optional)

- Button Eye Photo Control (PC)
- House Side Shield (H)
- 7-Pin Twist-Lock Receptacle (PCR7, C8 & C10 Capitals Only)
- 3-Pin Twist-Lock Receptacle (PCR3, C8 & C10 Capitals Only)

#### Housing

- Decorative Capital Housing Choices with 3" Slip Fitter\*

#### Finish

- Super Durable Polyester Powder Coat Finish. Custom Finishes Available, Including Patinas and All RAL Colors.

#### Listings & Ratings

- ETL Listed to UL 1598 Standard for Wet Location.

#### Warranty

- 5 Year Limited Warranty

EPA: 2.2  
Weight: 32 lbs (Max.)

**QUICK SHIP**  
Quick Ship Options In Red

### Order Information Example:

LEX2PAC856W4KU3A1T1NFBK

Model	Globe/Lens	Capital	LED Module	Voltage	Distribution	Bands & Cages	Spinning	Options	Final	Finish
<b>LEX2</b>										
<b>LEX2</b> =Lexington 2 Prismatic Globe Post Top	<b>PA</b> =Prismatic Acrylic <b>PP</b> =Prismatic Polycarbonate	<b>C1</b> =PLC1 <b>C2</b> =PLC2 <b>C3</b> =PLC3 <b>C4</b> =PLC4 <b>C5</b> =PLC5 <b>C6</b> =PLC6 <b>C7</b> =PLC7 <b>C8</b> =PLC8 <b>C9</b> =PLC9 <b>C10</b> =PLC10 <b>C11</b> =PLC11	See Lumen Output Chart	<b>U</b> =120-277V <b>H</b> =347/480V	<b>3</b> =Type III <b>5</b> =Type V	<b>A1</b> =DECA1 <b>A2</b> =DECA2 <b>A3</b> =DECA3 <b>A6</b> =Perforated Band with Cage <b>A7</b> =Flat Band w/Cage <b>N</b> =None	<b>T1</b> =T101 <b>T3</b> =T103 <b>T4</b> =T104 <b>N</b> =None	<b>PC</b> =Button Eye Photo Control <b>PCR3</b> =3 Pin Twist Lock Receptacle* <b>PCR7</b> =7 Pin Twist Lock Receptacle* <b>N</b> =None  *C8, C10 Capital Only *Photo Cell Not Included	<b>B</b> =GF2 <b>C</b> =GF3 <b>D</b> =GF4 <b>E</b> =GF5* <b>F</b> =GF6 <b>H</b> =GF8 <b>I</b> =GF9 <b>J</b> =GF10 <b>K</b> =GF12 <b>O</b> =GF17 <b>P</b> =GF18 <b>V</b> =GF24 <b>N</b> =None  *Black Finish Only	<b>STANDARD FINISHES</b> <b>BK</b> =Black <b>BZ</b> =Bronze <b>DBZ</b> =Dark Bronze <b>WH</b> =White <b>GR</b> =Green <b>SM</b> =Silver Metallic <b>GY</b> =Light Gray <b>TBK</b> =Textured Black <b>CC</b> =Custom Color (Consult Factory)



**LED POST TOP LUMINAIRES**

**Photometric Data**



**Opti-FLUX™ LED Light Engine**

**Opti-FLUX™ LED LIGHT ENGINE SPECIFICATIONS:**

**Lumen Output for Lexington 2**

CCT	LED Module	Input Watts	Efficacy Range	Type 3			Type 5			
				Solid Top	Light Lid	Perf Lid	Solid Top	Light Lid	Perf Lid	
5K	32W5K	37	103	115	3862	4103	4135	4086	4221	4288
	40W5K	46	105	117	4827	5129	5168	5108	5276	5359
	48W5K	55	106	118	5793	6155	6202	6129	6331	6431
	56W5K	62	108	120	6758	7181	7236	7151	7386	7503
	64W5K	71	109	121	7723	8207	8269	8173	8442	8575
	72W5K	79	110	122	8689	9233	9303	9194	9497	9647
	80W5K	87	111	124	9654	10258	10336	10216	10552	10719
	88W5K	94	112	125	10620	11284	11370	11237	11607	11791
96W5K	102	114	126	11585	12310	12404	12259	12663	12863	
4K	32W4K	37	96	106	3584	3808	3837	3792	3917	3979
	40W4K	46	98	108	4480	4760	4796	4740	4896	4974
	48W4K	55	99	109	5375	5712	5755	5688	5875	5968
	56W4K	62	100	111	6271	6664	6715	6636	6855	6963
	64W4K	71	101	113	7167	7616	7674	7584	7834	7958
	72W4K	79	102	114	8063	8568	8633	8532	8813	8952
	80W4K	87	103	115	8959	9520	9592	9480	9792	9947
	88W4K	94	104	116	9855	10472	10551	10428	10772	10942
96W4K	102	105	117	10751	11424	11511	11376	11751	11936	
3K	32W3K	37	87	96	3244	3447	3473	3432	3546	3602
	40W3K	46	88	98	4055	4309	4341	4291	4432	4502
	48W3K	55	89	99	4866	5170	5210	5149	5318	5402
	56W3K	62	91	101	5677	6032	6078	6007	6205	6303
	64W3K	71	92	102	6488	6894	6946	6865	7091	7203
	72W3K	79	93	103	7299	7755	7814	7723	7977	8103
	80W3K	87	94	104	8110	8617	8683	8581	8864	9004
	88W3K	94	94	105	8920	9479	9551	9439	9750	9904
96W3K	102	95	106	9731	10340	10419	10297	10637	10805	
27K	32W27K	37	86	95	3201	3401	3427	3387	3498	3553
	40W27K	46	87	97	4001	4251	4283	4233	4373	4442
	48W27K	55	88	98	4801	5101	5140	5080	5247	5330
	56W27K	62	90	100	5601	5951	5997	5927	6122	6219
	64W27K	71	91	100	6401	6802	6853	6773	6996	7107
	72W27K	79	91	101	7201	7652	7710	7620	7871	7995
	80W27K	87	92	102	8001	8502	8567	8467	8746	8884
	88W27K	94	93	103	8802	9352	9424	9313	9620	9772
96W27K	102	94	105	9602	10203	10280	10160	10495	10660	

**LED POST TOP LUMINAIRES**

**Capitals**



PLC1 - 8 3/4" High



PLC2 - 10 13/16" High



PLC3 - 6 7/8" High



PLC4 - 7 13/16" High



PLC5 - 9 15/16" High



PLC6 - 8 1/16" High



PLC7 - 8 3/8" High



PLC8 - 11 3/8" High



PLC9 - 14 1/4" High



PLC10 - 10 1/4" High



PLC11 - 15" High

**Bands & Cages**



A1 - Cast Aluminum Perforated Cage



A2 - Cast Aluminum Band



A3 - Cast Aluminum Cage



A6 - Cast Aluminum Cage w/ Perforated Band



A7 - Cast Aluminum Cage w/ Flat Band



A6M - Cage with Medallions\*

**\*A1, A6, and A7 are available with Medallions. Add M to the end of the part number.**



**LED POST TOP LUMINAIRES**

**Spinnings**



T1 - T101 Top Spinning



T3 - T103 Top Spinning



T4 - T104 Top Spinning

**Fixture Finials**



GF2 - 6"



GF3 - 6"



GF4 - 6"



GF5 (Plastic)  
 GF6 (Cast) - 4"



GF8 - 4"



GF9 - 4.25"



GF10 - 3.5"



GF12 - 2.75"



GF17 - 4"



GF18 - 2.75"



GF24 - 4.75"



## LED POST TOP LUMINAIRES

**Dimensions**

